

Diamond drill

230V~50Hz
2800 W
700 mm
1 1/4" 32 mm
1 1/4" 32 mm
1 1/4" 32 mm



Fitting core drill bits: see chapter 10
 $L_{pa} = 92,4 \pm 3,0$ dB; $L_{wa} = 105,4 \pm 3,0$ dB
 Fitting water tank: YT-86211

YATO	[W]	
YT-81983	2800	1
YT-81983BS	2800	1

Magnetic drill

1050 W
220-240V~50/60Hz
650 mm
11500 N
max Ø 30 mm
140 mm
DRILL COOLING CHŁODZENIE WIERTLA
STEEL TYP



YATO	[W]	
YT-820500	1050	1

Magnetic drill

1300 W
220-240V~50/60Hz
0-550 mm
11500 N
max Ø 35 mm
150 mm
DRILL COOLING CHŁODZENIE WIERTLA
STEEL TYP



YATO	[W]	
YT-820501	1300	1

Magnetic drill

1800 W
220-240V~50/60Hz
0-550 mm
MT2
THREADING FUNCTION FUNKCJA WYCIĘCIA
13800 N
max Ø 50 mm
180 mm
DRILL COOLING CHŁODZENIE WIERTLA
STEEL TYP



YATO	[W]	
YT-820502	1800	1

Vibrating concrete screed

230V~50Hz
240 W
6000/10000 mm
1m
AI
IPX4
FOLDABLE HANDLE SKŁADANY UCHWYT



$L_{pa} = 88,0 \pm 3,0$ dB; $L_{wa} = 96,0 \pm 3,0$ dB; $a_n = 4,3 \pm 1,5$ m/s²

YATO	[W]	Profile length	
YT-82611	240	1	1

Vibrating screed replacement blade

AI



For YT-82611

YATO	L [m]	
YT-82612	2	1
YT-82613	3	1

Concrete vibrator (motor and poker shaft)

230V~50Hz
2300 W
4000 mm
35 mm
4 m



$L_{pa} = <70$ dB; $L_{wa} = <85$ dB; $a_n = <2,5$ m/s²

YATO	[W]	
YT-82601	2300	1
YT-82601BS	2300	1

Poker shaft



YATO	Ø [mm]	L [m]	For	
YT-82595	35	3	YT-82600	1
YT-82596	35	4	YT-82601	1
YT-82597	25	1.2	YT-82600 YT-82604	4

Poker shaft



For YT-84827

YATO	Size	
YT-84828	Φ38MM, 6M	1
YT-84829	Φ45MM, 6M	1