

Metal cutting disc




• Application: concrete, brick, tile, masonry, stone, sandstone, refractory materials, limestone

YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	D [mm]	
YT-5920	115	22	13200	1.2	25/50
YT-5921	115	22	13200	2.5	25/200
YT-5922	115	22	13200	3.2	25/200
YT-5923	125	22	12200	1.2	25/200
YT-5924	125	22	12200	2.5	25/200
YT-5925	180	22	8600	1.5	25/50
YT-5926	180	22	8600	2.5	25/50
YT-5927	230	22	6500	2.0	25/50

YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	D [mm]	
YT-6110	125	22	12200	3.2	25/200
YT-6112	230	22	6500	3.2	25/50
YT-6113	300	32	5100	3.2	5/25
YT-61131	350	25	4400	3.5	25
YT-61132	355	25.4	4400	3.2	5/25
YT-6136	350	33.2	4400	3.5	1/25
YT-6137	400	32	3800	4.0	25



Inox cutting disc



YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	D [mm]	
YT-61009	100	16	15200	1.0	25/200
YT-6101	115	22	13200	1.2	25/200
YT-61025	125	22.23	12200	1.0	50/400
YT-6103	125	22	12200	1.2	25/200
YT-6104	125	22	12200	205	25/200

YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	D [mm]	
YT-6105	180	22	8600	1.5	25/50
YT-6107	230	22	6500	2.0	25/50
YT-61068	230	22	6600	1.8	25/100
YT-61091	355	25.4	4400	3.5	5/25

Diamond polishing disc for stoneware




For YT-82161

• Application: gres tile, granite, stone, concrete

YATO	Grit	Ø [mm]	max ω [min ⁻¹]	
YT-48200	D50	100	4500	50/300
YT-48201	D100	100	4500	50/300
YT-48202	D200	100	4500	50/300
YT-48203	D400	100	4500	50/300

YATO	Grit	Ø [mm]	max ω [min ⁻¹]	
YT-48204	D800	100	4500	50/300
YT-48205	D1500	100	4500	50/300
YT-48206	D3000	100	4500	50/300

Diamond grinding cup wheel



• Application: concrete, screed

YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	Size [mm]	For	
YT-60322	125	22.2	12200	5x9	YT-82110, YT-82101	30
YT-60323	180	22.2	6600	5x9	YT-82341, YT-82110	10

Metal grinding disc



• Depressed center

YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	D [mm]	
YT-6121	115	22	13200	6.0	25/100
YT-6124	125	22	12200	6.0	30/120
YT-6138	180	22	8600	6.0	15/30
YT-6126	125	22	12000	8.0	25/100
YT-6125	230	22	6500	6.0	5/30

Stone grinding disc



• Depressed center

YATO	ØA [mm]	Ød [mm]	max ω [min ⁻¹]	D [mm]	
YT-6133	125	22	12200	6.8	25/100