




Diamond blade



• Application: concrete, brick, tile, masonry, stone, sandstone, refractory materials, limestone

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-59961	115	22.2	12000	1.8	10	20/200
YT-59962	125	22.2	12000	2.0	10	20/100
YT-59965	230	22.2	6500	2.2	10	25
YT-60003	350	25.4	4400	3.4	10	10
YT-60004	400	25.4	3850	3.6	10	5

Diamond blade



• Application: reinforced concrete, glaze, clinker, brick, limestone

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-59981	115	22.2	12000	1.3	10	20/200
YT-59982	125	22.2	12000	1.3	10	20/100
YT-59985	230	22.2	6500	2.0	10	25

Diamond blade



• Application: concrete, reinforced concrete, brick, tile, masonry, stone, sandstone

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-6021	115	22.2	12000	2.2	5.3	20/200
YT-6022	115	22.2	12000	2.4	8	20/200
YT-6023	125	22.2	11000	2.6	8	20/160
YT-6024	180	22.2	8000	2.8	8	15/60
YT-6025	230	22.2	6500	3.1	8	10/40

Diamond blade



• Application: ceramic, glaze

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-59951	115	22.2	12000	1.6	10	20/200
YT-59952	125	22.2	12000	1.6	10	20/100
YT-59955	230	22.2	6500	2.2	10	25


Diamond blade



• Application: concrete, brick, calcium-silicate brick, tile, masonry, stone

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-60009	100	16	14000	2.1	8	20/200
YT-6001	115	22.2	12000	1.8	8	20/200
YT-6002	115	22.2	12000	2.1	8	20/200
YT-6003	125	22.2	11000	2.2	8	20/160
YT-6004	180	22.2	8000	2.5	8	15/60
YT-6005	230	22.2	6500	2.7	8	10/40

Diamond blade



YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-5983	300	25.4	5100	3.2	10.0	10
YT-5984	350	25.4	4300	3.2	10.0	5


Diamond blade



• Application: ceramic, glaze, glass, porcelain, ceramic tiles, composite hardest tiles, roof tiles

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-59971	115	22.2	12000	1.6	10	20/120
YT-59972	125	22.2	12000	1.6	10	20/100
YT-59975	230	22.2	6500	2.0	10	25

Diamond blade



• Application: ceramic, gres, glaze, glass, porcelain

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	D [mm]	H [mm]	
YT-6011	110	22.2	12000	2.0	5.3	20/200
YT-6012	115	22.2	12000	2.1	5.3	20/200
YT-6013	125	22.2	11000	2.2	5.3	20/160
YT-6014	180	22.2	8000	2.5	5.3	15/60
YT-6015	230	22.2	6500	2.7	5.3	10/40
YT-6016	180	25.4	8000	2.2	5.3	15/60
YT-6017	200	25.4	8000	2.2	5.3	10/40

Diamond grinding cup wheel



• Application: concrete, clinker, natural stone, screed

YATO	ØA [mm]	Ød [mm]	max C [min ⁻¹]	Segment size [mm]	
YT-6030	125	22.2	12200	5x7.5	20
YT-6031	180	22.2	8500	5x20	10
YT-6032	125	22.2	12200	4.5x20	20

